

Chris Craft Marine Engines

Model	HP	CYL	cu in	Bore	Stroke	RPM	Weight	Carburertor
A-70	225	V-8	824.67	5	5 1/4	2200	1625	updraft
A-70	250	V-8	824.67	5	5 1/4	2200	1625	downdraft
A-120	275	V-8	824.67	5	5 1/4	2300	1750	downdraft
A-120A	350					2800		
A	60	4	132.7	3 1/4	4	3200	465	updraft
B	60	4	132.7	3 1/4	4	3200	465	updraft
C	45	4				3200		
H	75	6	205.3	3 1/4	4 1/8	3200	595	updraft
K	85	6	221.4	3 3/8	4 1/8	3200	600	updraft
KA	95	6	221.4	3 3/8	4 1/8	3500	600	updraft
K	95	6	229.7	3 7/16	4 1/8	3200	660	updraft
K-100	100	6	229.7	3 7/16	4 1/8	3200	660	updraft
KB	121	6	221.4	3 3/8	4 1/8	3800		updraft
KL	105	6	236.6	3 7/16	4 1/4	3200	698	updraft
KLC	120	6	236.6	3 7/16	4 1/4	3800	703	updraft
KBL	131	6	236.6	3 7/16	4 1/4	3800	706	triple downdraft
KFL	131	6	236.6	3 7/16	4 1/4	3800	715	twin updraft
L	118	6	263.3	3 5/8	4 1/4	3200		
M	130	6	320.4	4	4 1/4	3000	880	updraft
MB	145	6	320.4	4	4 1/4	3400		
ML	145	6	339.2	4	4 1/2	3000		
MBL	158	6	339.2	4	4 1/2	3400		
MCL	175	6	339.2	4	4 1/2	3400	940	twin updraft
WB	200	6	404.3	4 1/4	4 3/4	3200	1260	twin updraft

Additional model designation codes include:

"O" = Opposite Rotation

"S" = 1.5:1 Reduction Gear

"R" = 2:1 Reduction Gear